Pressure and level transmitters

Ceramic Pressure Transmitter, Metri-Pack, G1/4 or 7/16-20UNF

Model CS-PT1100A

Compact ceramic piezo-resistive pressure transmitter, 0~5...50bar gauge, with 4~20mA output, ±1.0%F.S accuracy and a Packard Metri-Pack connector.



Range	Accuracy
0–5...50bar Gauge	**±1.0% F.S.**
Output	Supply voltage
4–20mA	**10–30VDC**

Features

- Ceramic piezo-resistive sensing element
- G1/4 or 7/16-20UNF pressure connection
- Medium temperature -30°C~120°C
- 10–30VDC supply
- Suitable for mass production

Applications

Air compressors, Hydraulic and pneumatic systems, Machinery manufacturing, General pressure measurement

Specifications

Performance parameters

Reference conditions	Temperature: 25°C, Power: 12VDC, RH: 45%~75%, Atmospheric pressure: 86KPa~106KPa
Pressure range	0–5...50bar Gauge
Output signal	4–20mA
Power supply (u+)	10–30VDC
Output load	≤ (U+ - 10) / 0.023Ω (MAX: 600Ω)
Over voltage	30VDC
Reverse voltage	-30VDC
Accuracy at room temperature	±1.0% F.S.
Medium temperature	-30°C~120°C


Ambient temperature	-20°C~85°C
Storage temperature	-40°C~100°C
Long-term stability	±0.5%F.S / year
Settling time	(10%~90%) ≤10ms
Overload pressure	≥ 150%F.S
Burst pressure	≥ 200%F.S
Pressure connection	G1/4, 7/16-20UNF


Ordering and support


Pricing, samples, lead time and custom versions: dwinsales@163.com, +86 181 0280 8901.

Guangzhou Dwin Technology Co., Ltd., 4th Floor, Building 2, No. 4 Xingye Road, Xiaowu Second Industrial Zone, Dongyong Town, Nansha District, Guangzhou, China. Specifications are typical values and may change without notice; confirm critical values with DWIN before design-in. Revision 2026-11.

Dimensions and wiring



Packard Metri-Pack	Pin	Definition
	A	Shield（PE）
	B	Power Supply+ (U+)
	C	Current Output (Io)



Drawings are for reference. Dimensions in millimetres unless stated.