IoT monitoring

Manhole Cover Movement Monitor, Internal Water Level, CAT.1

Model CS-iTWM-05D

Battery-powered manhole cover movement monitor with internal water level sensing, reporting over NB-IoT or CAT.1, with IP68 protection and alarm delay under 30s.



Range
0° ~ 180°

Frequency
B1/3/5/7/8/20/28

Protection
IP68

Features

- NB-IoT and CAT.1 transmission
- Alarm delay <30s at RSRP ≥ -105 dBm
- Non-rechargeable ER1450*3+SPC1520 battery
- Battery life ≥ 3years
- Operating temperature (-40–+85)°C

Applications

Manhole cover monitoring, Manhole water level monitoring

Specifications

Wireless	
Working frequency (CAT1)	B1/3/5/7/8/20/28
Working frequency (NB-IoT)	B3/B5/B8

Electrical	
Operating voltage	ER1450*3+SPC1520, non-rechargeable
Battery life	≥ 3years (No less than 3,000 items)
Maximum working current	<350mA
Sleeping current	<25.0uA

Performance	
Measuring range	0° ~ 180°
Alarm delay	<30s (signal environment is good, with RSRP≥ -105 dBm)

Mechanical	
Protection level	IP68
Shell material	PC+ABS (anti-aging, anti-corrosion, anti-collision materials)


Environmental	
Operating temperature	(-40–+85)°C
Storage temperature	(-40–+85)°C


Ordering and support


Pricing, samples, lead time and custom versions: dwinsales@163.com, +86 181 0280 8901.

Guangzhou Dwin Technology Co., Ltd., 4th Floor, Building 2, No. 4 Xingye Road, Xiaowu Second Industrial Zone, Dongyong Town, Nansha District, Guangzhou, China. Specifications are typical values and may change without notice; confirm critical values with DWIN before design-in. Revision 2026-11.

Dimensions and wiring







Drawings are for reference. Dimensions in millimetres unless stated.